

Threaded type

■ Brass & bronze

Excluded from 97/23/CE directive (article 1, § 3.2) - Max. pressure 16 bar up to 2", 10 bar above - Max. temperature 120°C.



206 - Brass body
 Stainless steel filter - Mesh 8/10°.

Ø	3/8"	1/2"	3/4"	1"	1"1/4"	1"1/2"	2"	2"1/2"
code	206003	206004	206005	206006	206007	206008	206009	206010



202 - Bronze body
 Stainless steel filter - Mesh 6/10°.
 203 - Bronze body - For gas
 Mesh 3/10°.



Ø	3/8"	1/2"	3/4"	1"	1"1/4"	1"1/2"	2"	2"1/2"	3"	4"
202 code	202003	202004	202005	202006	202007	202008	202009	202010	202011	202012
203 code	203003	203004	203005	203006	203007	203008	203009	203010	203011	203012

■ Steel

Use: for compatible common fluids of group 2 - 97/23/CE directive N° 1115 - Risk category II - Use : steam - Forged carbon steel A105 - Mesh 8/10° - Max. pressure 55 bar - Max. temperature 300°C.

231 - BSP threaded
 232 - Socket Welding
 234 - NPT threaded



Ø	1/4"	3/8"	1/2"	3/4"	1"	1"1/4"	1"1/2"	2"
231 code	231002	231003	231004	231005	231006	231007	231008	231009
232 code	232008	232010	232015	232020	232025	232032	232040	232050
234 code	234002	234003	234004	234005	234006	234007	234008	234009

■ Stainless steel

Use: for compatible common fluids of group 2 - 97/23/CE directive N° 0035 - Risk category II - Mesh 10/10° - Max. pressure 16 bar - Max. temperature 200°C.

230 - Stainless steel 316



Ø	1/4"	3/8"	1/2"	3/4"	1"	1"1/4"	1"1/2"	2"
code	230002	230003	230004	230005	230006	230007	230008	230009

Flanged type

For compatible common fluids of group 2 - Concerned by article 3, § 3 from 97/23/CE directive.

220 - Cast iron

PN 16 up to DN 200, PN 10 above - SS filter - DIN 3202 - NF 29354

Max. pressure 16 bar - Max. temperature 120°C.



DN	15	20	25	32	40	50	65	80	100	125	150	200	250	300
Mesh	1	1	1	1	1	1,5	1,5	1,5	3	3	3	3	3	3
face to face	130	150	160	180	200	230	290	310	350	400	480	600	730	850
code	220015	220020	220025	220032	220040	220050	220065	220080	220100	220125	220150	220200	220250	220300

For compatible common fluids of group 2 - 97/23/CE directive N° 0062 - Risk category I up to DN 80, risk category II above.



235 - Carbon steel

PN 25/40 - Mesh 8/10° - DIN 3202 - NF 29354 - Max. pressure 25 bar - Max. temperature 250°C.

DN	15	20	25	32	40	50	65	80	100
face to face	130	150	160	180	200	230	290	310	350
code	235015	235020	235025	235032	235040	235050	235065	235080	235100

For compatible common fluids of group 2 - 97/23/CE directive N° 0035 - Risk category I up to DN 50, risk category II above.



240 - Stainless steel 316

PN 16 - DIN 3202 - NF 29354 - Max. pressure 16 bar - Max. temperature 180°C.

DN	15	20	25	32	40	50	65	80	100	125	150	200
Mesh	8/10°	8/10°	8/10°	8/10°	8/10°	8/10°	16/10°	16/10°	16/10°	16/10°	16/10°	16/10°
face to face	130	150	160	180	200	230	290	310	350	400	480	600
code	240015	240020	240025	240032	240040	240050	240065	240080	240100	240125	240150	240200