

Zawory iglicowe, klinowe

Medynski

Automatyka Przemysłowa

ul. Naddawki 11 05-822 Milanówek
tel.: 22 498 12 45 | +48 503 191 518
faks: 22 425 97 45 | 22 724 84 78
email: armatura@medynski.pl | www.medynski.pl

Zawory iglicowe

For compatible common fluids of group 2 -
Concerned by article 3, § 3 from 97/23/CE directive.

482 - Bronze

Brass hat - Max. pressure 10 bar - Max. temperature 150°C.



| Ø | 1/4" | 3/8" | 1/2" | 3/4" |
|------|--------|--------|--------|--------|
| code | 482002 | 482003 | 482004 | 482005 |

481 - Stainless steel

Max. pressure 400 bar - Max. temperature 200°C.



| Ø | 1/4" | 3/8" | 1/2" | 3/4" |
|------|--------|--------|--------|--------|
| code | 481002 | 481003 | 481004 | 481005 |

484 - Forged steel - NPT threaded

483 - Forged steel - BSP threaded

486 - Forged steel - Butt welding

3000 lbs - Max. pressure 200 bar - Max. temperature 250°C.



| Ø | 1/4" | 3/8" | 1/2" | 3/4" | 1" |
|----------|--------|--------|--------|--------|--------|
| 484 code | 484002 | 484003 | 484004 | 484005 | 484006 |
| 483 code | 483002 | 483003 | 483004 | 483005 | 483006 |
| 486 code | 486008 | 486010 | 486015 | 486020 | 486025 |

Zawory klinowe

Female - Female

Excluded from 97/23/CE directive (article 1, § 3.2).

102 - Brass body

Max. pressure 16 bar up to 2", 10 bar above - Max. temperature 80°C - PN 16.



| Ø | 1/4" | 3/8" | 1/2" | 3/4" | 1" | 1 1/4" | 1 1/2" | 2" | 2 1/2" | 3" | 4" |
|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| code | 102002 | 102003 | 102004 | 102005 | 102006 | 102007 | 102008 | 102009 | 102010 | 102011 | 102012 |

Concerned by article 3, § 3 from 97/23/CE directive.

146 - Bronze body

Max. pressure 16 bar up to 2", 10 bar above - Max. temperature 80°C - PN 16.



| Ø | 1/4" | 3/8" | 1/2" | 3/4" | 1" | 1 1/4" | 1 1/2" | 2" | 2 1/2" | 3" | 4" |
|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| code | 146002 | 146003 | 146004 | 146005 | 146006 | 146007 | 146008 | 146009 | 146010 | 146011 | 146012 |

Flanged type

Excluded from 97/23/CE directive (article 1, § 3.2).

150 - Cast iron body

DIN 3352 - PN 10 - Max. pressure 10 bar up to DN 150, 6 bar above - Max. temperature 120°C.



| Ø | 40 | 50 | 65 | 80 | 100 | 125 | 150 | 200 | 250 | 300 |
|--------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| face to face | 140 | 150 | 170 | 180 | 190 | 200 | 210 | 230 | 250 | 270 |
| code | 150040 | 150050 | 150065 | 150080 | 150100 | 150125 | 150150 | 150200 | 150250 | 150300 |